

COATING SPECIFICATION

SUBSTRATE: Interior Plaster - Repaint

COATING:

1st coat: Colourtrend Interior Matt in desired colour

2nd coat: Colourtrend Interior Matt in desired colour*

SURFACE PREPARATION:

- Ensure surface is clean, dry and sound.
- Wash with sugar soap solution, rinse with clean water to remove sugar soap and allow to dry.
- Fill any holes with appropriate filler. Fill all gaps which are subject to movement, e.g. plaster to door-frame, plaster to skirting, with elastomeric acrylic caulk (we recommend the Allpro range).
- Sand lightly to ensure flush finish. Remove dust.

APPLICATION:

- Brush, roll or spray
- Ensure good drying conditions and ventilation during application and drying.
- Do not apply if surface or ambient temperature is below 10°C.

NOTES:

- Two coats should suffice in many applications. A third coat may be necessary when there is a significant colour change.
- For a soft-sheen finish the second coat should be replaced with Colourtrend Soft Sheen.
- The information above applies when the old coating is of an emulsion type and compatible with Colourtrend decorative emulsions. For application to any other coating, e.g. alkyd paints, adhesion and compatibility should be checked in advance by testing a trial area.

*Some colours may require extra coats



INFINITE COLOUR *from* IRELAND

Colourtrend, Maynooth Road, Celbridge, Co Kildare, W23 X7R8, Ireland
t: +353 1 6288224 f: +353 1 6272205 e: info@colourtrend.ie

IMPORTANT NOTE: The information contained in this specification sheet is not intended to be conclusive. It is for guidance and is given in good faith. Whilst we attempt to ensure that all advice we give about our products, whether in this sheet or otherwise, is correct, we have no control over the quality or condition of the substrate or the many factors affecting the use and application of this product. Many such factors are beyond our control and it is always good practice to conduct a trial area in advance to ensure a satisfactory result.